

BEST PACKAGING



**Certified Refurbished
3M-Matic™ Side Belt
Adjustable Case Sealer 800a3**

Best Packaging Inc
(888) 930-BEST
BestPackaging.com

Certified Refurbished 3M-Matic™ Side Belt Adjustable Case Sealer 800a3

Located on each side of the 3M-Matic™ Automatic Adjustable Case Sealer 800a, traction-grip drive belts center and stabilize a variety of RCS heights. The side drives are repositionable to provide stability for taller boxes.

FEATURES

- Height and width adjustments for a wide range of RSC sizes
- Designed for use with 1.5"-2" (36-48mm) Scotch® Box Sealing Tapes; model 800a3 is available for use with 3" (72mm) tape
- Dual masts and dual crossbars for taping head stability
- Centrally-located emergency stop for better access
- Twin gear motor drives for dependability with cases up to 85 lbs (38 kg)
- Top flap compression rollers to close flaps for improved seal

3M-Matic™ Adjustable Case Sealer 800ab is available for sealing bottom flaps only.

Box Capacities

	Length	Width	Height
Minimum	6" (152 mm)	4.5" (114 mm)	4.75" (121 mm)
Maximum	Unlimited	21.5" (546 mm)	24.5" (622 mm)
Box Weight	5-85 lbs (3-38 kg)		

Note: The 3M-Matic™ Automatic Adjustable Case Sealer 800a3 can accommodate most boxes within the size range listed here. However, if:

Box Length in Direction of Seal

Box Height
is less than .75

Boxes should be test run to ensure proper machine performance.

Product Use: User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application

The detail of the product(s), descriptions or specifications (for example weight, color, size, etc.) are only approximate values based upon a "standard model" of the representative product(s)/feature(s). There may be slight variations in the actual product design, dimensions, and functionality as compared to the information shown on our website and/or any supplementary product documentation, including but not limited to product brochures and spec sheets.


Specifications (See fig. 3 to the right)


	Maximum	Minimum
Tape Sizes	2" (48 mm)	3" (72 mm)
Machine Weight	350 lbs (160 kg)	
Width	38.5" (978 mm)	
Length	36" (914 mm)	
Height	53" (1346 mm)	86" (2184)
A**	18" (457 mm)	
B	24" (610 mm)	35" (889 mm)
C***	4" (102 mm)	
F	24.5" (622 mm)	
Electrical	115V 60 Hz 2.8A 315 watts 8'	
Operating Rate	Up to 40 per minute	
Drive Belt Speed	100 fpm (0,5 m/s)	

* Uncrated

** Optional infeed/exit
conveyors

*** Optional Casters





BEST PACKAGING®

WHY WE'RE THE BEST



Since 1997, we have been consulting, designing and implementing packaging solutions to offer the best for your operations. We represent a variety of equipment manufacturers, so as to ensure we're matching the right solution for your packaging needs. We only align ourselves with quality brands to make sure we are delivering the best value. It is our goal to provide the highest quality service to make your job easier and more productive.

Over 150 years of industrial experience, collectively.

We represent multiple brands and our analysis is unbiased. We can match the best systems with your needs based on the versatility of the job.

With preventative maintenance, operator training, and 24/7 support, we're with you every step of the way!

Steve Kudia, Owner of Best Packaging, serves on the ASTM committee. As part of a prestigious worldwide network of technical experts, he aims to make sure processes stay efficient by monitoring trends and educating customers on how they can improve their performance.

Equipment We Sell & Service

Stretch Wrappers
Shrink Wrappers
Tray and Case Loaders
Tray & Case Erectors
Corrugated Case Formers
Conveyors
Palletizers
Robotics
Strappers & Banders
Much, much more!

 @BestPackagingInc

 @Best_Packaging

 /Best-Packaging-Inc