

# **BEST PACKAGING**



**Certified Refurbished  
StraPack D-53 PLT Portable  
Pallet Strapping System**

**Best Packaging Inc  
(888) 930-BEST  
BestPackaging.com**

## Certified Refurbished StraPack D-53 PLT Portable Pallet Strapping System

The D-53 PLT is a portable pallet strapping system which can be used with standard or heavier polypropylene strapping. This machine is ideal for anyone, especially for low pallets (as low as 14"). This machine has the ability to reduce the time it takes to strap a pallet by about two thirds, compared to hand tools. To operate, simply push the track into the pallet void and feed the strap with the touch of a button. Then, insert the tip of the strap into the machine. The operation will be completed within seconds. The arch track is extremely versatile. It is retractable via hand-crank, and there are two different height settings. The track also folds into a vertical position for easy storage. The D-53 PLT even offers edge protection insertion by switching from automatic to manual mode.

### FEATURES

- Simple Height Adjustment
- 4-Way Pallet Entry
- Easy Orientation
- Lower Sealing for Small Pallet
- Versatile Tension Capability (Auto/Manual Tension Mode)




Digital Readers: Click the image to watch the D-53 PLT in action

The detail of the product(s), descriptions or specifications (for example weight, color, size, etc.) are only approximate values based upon a "standard model" of the representative product(s)/feature(s). There may be slight variations in the actual product design, dimensions, and functionality as compared to the information shown on our website and/or any supplementary product documentation, including but not limited to product brochures and spec sheets.

## Certified Refurbished StraPack D-53 PLT Portable Pallet Strapping System

Machine Specifications			
	Length	Width	Height
Machine Dimensions	29 4/5" (756 mm)	87" (2210 mm)	39 4/5" (1012 mm)
Appx Machine Weight	220 lbs (100 kg)		
Bayonet Height	3/5", 1" (15, 25 mm)		
Minimum Package Height	15" (380 mm)		
Strap Width	1/4", 3/8", 1/2", 5/8" (6, 9, 12, 15.5 mm)		
Strap tension	20-156 lbs (9-70 kgf)		
Sealing Method	Heat Seal		
Power Supply	1 Ph, 110 V, 60 Hz		





# BEST PACKAGING®

## WHY WE'RE THE BEST

Since 1997, we have been consulting, designing and implementing packaging solutions to offer the best for your operations. We represent a variety of equipment manufacturers, so as to ensure we're matching the right solution for your packaging needs. We only align ourselves with quality brands to make sure we are delivering the best value. It is our goal to provide the highest quality service to make your job easier and more productive.

Over 150 years of industrial experience, collectively.

We represent multiple brands and our analysis is unbiased. We can match the best systems with your needs based on the versatility of the job.

With preventative maintenance, operator training, and 24/7 support, we're with you every step of the way!

Steve Kudia, Owner of Best Packaging, serves on the ASTM committee. As part of a prestigious worldwide network of technical experts, he aims to make sure processes stay efficient by monitoring trends and educating customers on how they can improve their performance.

### Equipment We Sell & Service

- Stretch Wrappers
- Shrink Wrappers
- Tray and Case Loaders
- Tray & Case Erectors
- Corrugated Case Formers
- Conveyors
- Palletizers
- Robotics
- Strappers & Banders
- Much, much more!



@BestPackagingInc



@Best\_Packaging



/Best-Packaging-Inc